

REV.

DESCRIPTION

DATE

YYYY/MM/DD

THESE DRAWINGS ARE THE PROPERTY OF *Tt CO.,LTD.* AND CONTAINS CONFIDENTIAL AND TRADE SECRET INFORMATION.AND SHALL NOT BE REPRODUCED, COPIED OR USED IN ANY MANNER WITHOUT THE PRIOR WRITER CONSENT OF *Tt CO.,LTD.*

CONN	PIN	COLOR	OUTPUT	WIRE AWG	LENGTH
P1B	1	ORANGE	+3.3V	16	23.6"±1.0" (600±25)
	2	ORANGE	+3.3V	16	
	3	BLACK	GND	16	
	4	RED	+5V	16	
	5	BLACK	GND	16	
	6	RED	+5V	16	
	7	BLACK	GND	16	
	8	GRAY	PG	18	
	9	PURPLE	+5VSB	16	
	10	YELLOW/BLACK	+12V1	16	
	11	YELLOW/BLACK	+12V1	16	
	12	ORANGE	+3.3V	16	
	13	ORANGE	+3.3V	16	
	14	BLUE	-12V	22	
	15	BLACK	GND	16	
	16	GREEN	PS-ON	16	
	17	BLACK	GND	16	
	18	BLACK	GND	16	
	19	BLACK	GND	16	
	20	NC			
	21	RED	+5V	16	
	22	RED	+5V	16	
	23	RED	+5V	16	
	24	BLACK	GND	16	
P2A	1	BLACK	GND	16	23.6"±1.0" (600±25)
	2	BLACK	GND	16	
	3	BLACK	GND	16	
	4	BLACK	GND	16	
	5	YELLOW/BLACK	+12V1	16	
	6	YELLOW/BLACK	+12V1	16	
	7	YELLOW/BLACK	+12V1	16	
	8	YELLOW/BLACK	+12V1	16	
P2B	1	BLACK	GND	16	23.6"±1.0" (600±25)
	2	BLACK	GND	16	
	3	BLACK	GND	16	
	4	BLACK	GND	16	
	5	YELLOW/BLACK	+12V1	16	
	6	YELLOW/BLACK	+12V1	16	
	7	YELLOW/BLACK	+12V1	16	
	8	YELLOW/BLACK	+12V1	16	
P3A/P3A2	1	YELLOW/BLACK	+12V1	16	21.7"±1.0" (550±25)
	2	YELLOW/BLACK	+12V1	16	
	3	YELLOW/BLACK	+12V1	16	
	4	BLACK	GND	16	
	5	BLACK	GND	16	
	6	BLACK	GND	16	
	7	BLACK	GND	16	
	8	BLACK	GND	16	
P3A1/P3A3	1	YELLOW/BLACK	+12V1	16	5.9"±1.0" (150±25)
	2	YELLOW/BLACK	+12V1	16	
	3	YELLOW/BLACK	+12V1	16	
	4	BLACK	GND	16	
	5	BLACK	GND	16	
	6	BLACK	GND	16	
	7	BLACK	GND	16	
	8	BLACK	GND	16	
P3A4/P3A5/P3A6/P3A7	1	YELLOW	+12V2	16	21.7"±1.0" (550±25)
	2	YELLOW	+12V2	16	
	3	YELLOW	+12V2	16	
	4	BLACK	GND	16	
	5	BLACK	GND	16	
	6	BLACK	GND	16	
	7	BLACK	GND	16	
	8	BLACK	GND	16	
P4A/P4A1/P4A2/P4A3/P4A4/P4A5/P4A6/P4A7	1	YELLOW	+12V2	16	21.7"±1.0" (550±25)
	2	BLACK	GND	16	
	3	BLACK	GND	16	
	4	RED	+5V	16	
	1	YELLOW	+12V2	16	
	2	BLACK	GND	16	
	3	BLACK	GND	16	
	4	RED	+5V	16	
P4B*	1	RED	+5V	22	5.9"±1.0" (150±25)
	2	BLACK	GND	22	
	3	BLACK	GND	22	
	4	YELLOW	+12V2	22	
	1	ORANGE	+3.3V	16	
	2	BLACK	GND	16	
	3	RED	+5V	16	
	4	BLACK	GND	16	
P5A/P5A3/P5A6	1	ORANGE	+3.3V	16	21.7"±1.0" (550±25)
	2	BLACK	GND	16	
	3	RED	+5V	16	
	4	BLACK	GND	16	
	5	YELLOW	+12V2	16	
P1B1/P1B2/P1B3/P1B4/P1B5/P1B6	1	ORANGE	+3.3V	16	3.93"±1.0" (100±25)
	2	BLACK	GND	16	
	3	RED	+5V	16	
	4	BLACK	GND	16	
	5	YELLOW	+12V2	16	

REV.

④

SCALE

1 : 1

UNIT

mm

GENERAL TOLERANCE

A

B

0.0 ~ 5

± 0.2

± 0.1

5.0 ~ 20

± 0.3

± 0.2

20.0 ~ 50

± 0.5

± 0.3

50.0 ~ 200

± 0.9

± 0.4

200.0 ~

± 1.3

± 0.5

ANGLE

± 3°

± 1°

Tt®

Thermaltake Technology Co., Ltd